

# ARTICLE 9043 1.4006 TX T-DRILL, VIS À TERRASSE À TÊTE FRAISÉE BOMBÉE, ENCOCHE

ITEM 9043 1.4006 TX  
T-DRILL, RSD CSK HEAD TERRACE SCREWS, CUTTING POINT



## APPLICATIONS:

Idéale pour toutes les entreprises de transformation du bois (charpenteries, construction en bois) ainsi que tous les jardiniers et paysagistes pour la fixation des bois de terrasse et des passerelles d'embarquement. La solution parfaite également dans les bois durs tels que le bangkirai, le massaranduba, etc.

Une profondeur de vissage de 4 fois le diamètre est requise. Une profondeur de vissage de 8 fois le diamètre serait l'idéal selon la nature du bois.

## USES:

*Ideal for all companies involved in wood processing (carpenters, timber construction) and all horticulturists and landscapers for fastening timbers and landing stages. Also the ideal solution for hardwoods such as Bankirai, Massaranduba, and many more.*

*A minimum screw-in depth of 4 x the diameter must be ensured. A screw-in depth of 8 x the diameter should be achieved depending on the wood.*

## CARACTÉRISTIQUES:

- Tête renforcée
- Nervures coupantes
- Tige stabilisée
- Nouvelle disposition des flancs de filetage
- Encoche
- Nervures de fraisage sous la tête
- Entraînement TX à six lobes internes
- Acier inoxydable martensitique trempé (1.4006)
- Revêtement glissant spécial

## FEATURES:

- Reinforced head
- stripping ribs
- Stabilised shaft
- New kind of threaded flank arrangement
- cutting point
- ribs under the head
- TX driving feature
- Martensitic stainless steel hardened (1.4006)
- Special smooth coating

d d	l l	b b	dk dk	k k	Entraînement Drive size	Référence Item Number	
5	40	26	8	3	TX25	9043400650 40	100
	50	36	8	3	TX25	9043400650 50	100
	60	40	8	3	TX25	9043400650 60	100
	70	50	8	3	TX25	9043400650 70	100
	80	50	8	3	TX25	9043400650 80	100

