



DIN 444

Désignation :

une vis à œil de \varnothing 16 filet métrique normal et de 140 mm de longueur L = DIN 444 M16 x 140.

d	M5	M6	M8	M10	M12	M16	M20	M24	M27	M30
d2	5	6	8	10	12	16	18	22	25/25 (')	27/28 (')
d3 max	12	14	18	20	25	32	40	45	50	55
s max	6/8	7/9	9/11	12/14	14/17	17/19	22/24	25/28	27/30	30/34
b	x	16	18	22	26	30	38	46	54	60
	y	—	—	28	32	36	44	52	60	66
	z	—	—	—	—	49	57	65	73	79
L mm	Poids en kg aux 1000 pièces									
X	30	7,93								
	40	9,47	13,7	25						
	50	11	15,9	28,9	39,1					
	60	12,6	18,1	32,8	45,3	71,4				
	70	14,1	20,3	36,8	51,5	80,3	149			
Y	80	15,7	22,6	40,7	57,6	89,2	164			
	90		23,7	44,7	63,8	98,1	180			
	100			48,6	70	106	196	334	454	
	120			56,5	82,3	124	228	383	524	618
	140			64,4	94,5	142	259	433	596	708
Z	150				101	151	275	457	631	753
	160					160	281	482	667	798
	180					178	322	531	738	888
	200					195	354	581	809	978
	220					211	383	624	868	1060
Emball.	240					229	414	674	939	1140
	260					247	446	723	1010	1230
	280									1320
	300									1400
	300									1810

