


**DIN 928 - 928 C - 929**

**Désignation :**


un écrou à souder, carré, avec collerette de centrage,  $\varnothing$  8 mm, filet métrique normal = DIN 928 C M8.

**DIN 928 carré**




d	s	e	m	Poids en kg aux 1000 p.	Emball.
M4	7	9	3,5	0,81	500
M5	9	12	4,2	1,70	
M6	10	13	5	2,40	
M8	14	18	6,5	6,60	
M10	17	22	8	11,3	200
M12	19	25	9,5	16,6	

**DIN 928 C carré avec collerette de centrage**



d	$\varnothing$ maxi. coller. d3	s	e	m	Poids en kg aux 1000 p.	Emball.
M5	7	9	12	4,2	1,79	500
M6	8	10	13	5	2,52	
M8	11,2	14	18	6,5	6,83	
M10	14	17	22	8	11,87	200
M12	16	19	25	9,5	17,43	

**DIN 929 hexagonal**



d	Collerette d2	s	e	m	Poids en kg aux 1000 p.	Emball.
M4	6	9	10,5	3,5	1,13	500
M5	7	10	11,5	4	1,73	
M6	8	11	12,7	5	2,50	
M8	10,5	14	16,2	6,5	5,27	
M10	12,5	17	19,6	8	9,58	200