





6-Lobe Pin - Countersunk Self Drilling Screws



Drive Shape



1/2 Way



Security Rating



Self Drilling



Self Drilling Screws Technical Info (mm)

HEAD STYLE		GAUGE	No. 8	No. 10	No. 12
			4.2mm	4.8mm	5.5mm
COUNTERSUNK HEAD			7.9	9.3	10.6
			3.0	3.2	3.7
POINT SIZE			2	3	3
MATERIAL THICKNESS Mild Steel up to (mm)			1 + 2	2 + 2	2 + 3

All sizes shown are without min and max tolerances and are guide sizes.

Material and Finish

Material:	Steel C1022
Heat Treatment:	Hardened
Finish:	Delta Protekt

Part Numbers, Size & Tooling

GAUGE	LENGTH	1/2'	3/4'	1"	1 1/2"	2"	DRIVER SIZE
		13mm	19mm	25mm	38mm	50mm	
8	4.2mm	RTCD08D -DP	RTCD08F -DP	RTCD08G -DP	RTCD08I -DP		T20
10	4.8mm		RTCD10F -DP	RTCD10G -DP	RTCD10I -DP	RTCD10J -DP	T25
12	5.5mm			RTCD12G -DP	RTCD12I -DP	RTCD12J -DP	T27



Pack Weight (100pcs) & Box Type

GAUGE	LENGTH	1/2"	3/4"	1"	1 1/2"	2"	DRIVER SIZE
		13mm	19mm	25mm	38mm	50mm	
8	4.2mm	Box 9 150g	Box 9 195g	Box 12 235g	Box 18 330g		T20
10	4.8mm		Box 12 270g	Box 12 320g	Box 18 445g	Box 18 550g	T25
12	5.5mm			Box 18 450g	Box 18 600g	Box 22 745g	T27

*All parts Packed in 100pcs - Please see below Pack Dimension guide for sizes

Pack Dimensions Guide

DIMENSION	BOX SIZE	BOX 9	BOX 12	BOX 18	BOX 22	BOX 27	BOX 30	BOX 32
	A		51mm	57mm	71mm	81mm	89mm	101mm
B		32mm	36mm	47mm	54mm	68mm	76mm	82mm
C		55mm	66mm	90mm	111mm	124mm	128mm	171mm

