



REF: DIN 963

D1	M1.6	M2	M2.5	M3
D2	3.00	3.8	4.7	5.6
K max	0.96	1.2	1.5	1.65
N	0.4	0.5	0.6	0.8
t min	0.32	0.4	0.5	0.8
Pitch	0.35	0.4	0.45	0.5

Lengths and material available

D1	M1.6	M2	M2.5	M3
3	▼ ● ◆	▼ ● ◆	▼ ● ◆	
4	▼ ● ◆	▼ ● ◆	▼ ● ◆	
5	▼ ● ◆	▼ ● ◆	▼ ● ◆	▼ ● ◆
6	▼ ● ◆	▼ ● ◆	▼ ● ◆	▼ ● ◆
8	▼ ● ◆	▼ ● ◆	▼ ● ◆	▼ ● ◆
10	▼ ● ◆	▼ ● ◆	▼ ● ◆	▼ ● ◆
12	▼ ●	▼ ● ◆	▼ ● ◆	▼ ● ◆
14	▼	●	▼ ●	▼ ●
16	▼	▼ ●	▼ ● ◆	▼ ● ◆
18			▼ ●	▼ ●
20		▼ ●	▼ ●	▼ ● ◆
22			●	▼ ● ◆
25			▼ ●	▼ ● ◆
28				
30			●	▼ ● ◆
35				▼ ● ◆
40			●	▼ ● ◆
45				▼ ●
50				▼ ● ◆

▼ = Stainless Steel A2 ● = Steel 4.8 Zinc & Clear ◆ = Brass Stainless Steel A4 also available.